ANVIZ
POWERING SMARTER WORLD

# W1 PRO

## Colorful Screen Fingerprint, RFID Time & Attendance Terminal




Cloud

WiFi

Linux

Battery

W1 Pro is the new generation fingerprint time attendance terminal based on Linux platform and supports cloud application. W1 Pro houses 2.8-inches color LCD and full capacitive touch keypads along with touch optical fingerprint sensor Full upgrade for W series with battery will power your business anytime and anywhere. The webserver function realizes the easily self management of the device

# W1 PRO

Colorful Screen Fingerprint, RFID Time & Attendance Terminal

## Features

### 1Ghz Linux Based CPU

The new Linux based 1Ghz processor ensures the 1:3000 comparison time less than 0.5 second.

### Battery

The long life battery ensuring up to 10 hours portable application.

### Touch Active Fringerprint Sensor

The touch active sensor ensures the quick response for each detection and saving the total power consumption of the device.

### WIFI

The WiFi function ensures power on to work, and realize the flexible installation of the device.

### Touch Active Keypad

The touch active sensor ensures the best user experiences for and saving the total power consumption of the device.

### Colorful LCD Screen

The Colorful LCD screen ensures the best interaction and user experiences and can also provide clear notifications to the users.

### Webserver

The Webserver ensures the easily quick connection and self management of the device


### Cloud application


The web based cloud application let you access to the device by any mobile terminal from anytime and anywhere.

## Key Specifications

| | |
|---|---|
| User | 3000 |
| Card | 3000 |
| Record | 100000 |
| Communication | TCP/IP, Mini USB & USB Host,Optional WiFi |
| Identification mode | Finger, password, card (Standard EM card, optional Mifare card) |
| Identification speed | <0.5s |
| Card reading distance | "1~5cm ( 125KHz), 13.56MHz >2CM ) for standard CR80 card" |
| WebServer | support |
| CPU | Linux 1G |
| RFID card | Optional EM and Mifare |
| working Temperature | -30°C~60°C |
| Humidity | 20% to 90% |
| Power | DC12V/Optional Battery |
| | |

## System configurations





**Anviz Global Inc.**

41656 Christy Street Fremont , Fremont, CA,94538

Tel: 408-2637700 | Toll-free:1-855-268-4948 | Inquiry: sales@anviz.com | www.anviz.com



©2019 Anviz Gloabl Inc. Anviz and identifying product names and numbers herein are registered trademarks of Anviz Global Inc. All non-Anviz brands and product names are trademarks or registered trademarks of their respective companies. Product appearance, build status and/or specifications are subject to change without notice.

Due to the consistent improvement of the product, this specification and appearance are subject to change without notice.